

SERIE VS - VSV - VSI



Vaso d'espansione con membrana intercambiabile per impianti solari.
Expansion vessel with replaceable membrane for solar heating installations.
Vase d'expansion à vessie remplaçable pour installations chauffage solaires.
Druckausdehnungsgefäß mit austauschbarer Membrane für Solaranlagen.
Vaso de expansión con membrana recambiable para circuitos solares.

Temperatura d'esercizio
Working temperature
Température d'exercice
Betriebstemperatur
Temperatura de trabajo

- 10° C
+ 140° C

Colore della verniciatura esterna
External finish color
Couleur de la peinture externe
Externe Beendenfarbe
Color pintura exterior

RAL 9010

Membrana in gomma
Rubber membrane
Vessie en gomme
Gummimembrane
Membrana en goma

EPDM HT
alta temperatura
high temperature
haute temperature
Hochtemperatur

Controflangia zincata - Counter flange galvanized
Contre-bride galvanisé - Gegenflansch verzinkt - Contra brida galvanizada



Garanzia sul prodotto mesi: - Warranty months:
Garantie mois: - Monate Garantie: - Garantía meses:

24

Modello Model Modèle Model Modelo	Codice Code Code Code Código	Altezza Height Hauteur Höhe Altura H (mm)	Diametro Diameter Diamètre Durchmesser Diámetro Ø (mm)	Lunghezza Length Longeur Länge Longitud L (mm)	Pressione massima d'esercizio Maximun working pressure Pression maximale d'exercice Maximaler Betriebsdruck Presión máxima de trabajo (bar)	Pressione di precarica standard Standard precharge pressure Pression de précharge standard Vordruck Presión de precarga estándar (bar)	Imballo Packing Emballage Verpackung Embalaje (mm)	Attacco Connection Raccordement Anschluss Conexión (inch)
VS8	AAEPLOOW01BA1	316	200	-	10	2,5	(Pz1) 220X225X335	3/4 "
VS12	AAFPL0OW01BA1	295	280	-	10	2,5	(Pz1) 280X285X335	3/4 "
VS18	AAGPLOOW01BA1	430	280	-	10	2,5	(Pz1) 290X290X450	3/4 "
VS24	AAIPLOOW01DA1	483	280	-	10	2,5	(Pz1) 290X290X510	3/4 "
VSV35	AAJPL01W01DA1	450	365	-	10	2,5	(Pz1) 380X400X460	3/4 "
VSV50	AAKPL01W01DA1	582	365	-	10	2,5	(Pz1) 380X400X590	3/4 "
VSV80	AAMPL01W01EA1	717	415	-	10	2,5	(Pz1) 430X450X730	1 "
VSV100	AANPL01W01EA1	675	495	-	10	2,5	(Pz1) 510X540X700	1 "
VSV150	AAPPL01W01EA1	790	550	-	10	2,5	(Pz1) 570X610X850	1 "
VSV200	AAQPL01W21EA1	1085	600	-	10	2,5	(Pz1) 610X620X1111	1 "
VSV300	AASPL01W21EA1	1212	650	-	10	2,5	(Pz1) 670X680X1290	1 "
VSV500	AAUPL01W21FA1	1438	750	-	10	2,5	(Pz1) 750X770X1510	1 1/4 "

Vaso di raffreddamento per impianti solari. - Cooling vessel for solar heating installations.
Réservoir de refroidissement pour installations chauffage solaires.
Abkühlgefäß für Solaranlagen. - Vaso de enfriamiento para circuitos solares.

Senza membrana
Without membrane
Sans vessie
Ohne Membrane
Sin Membrana

Modello Model Modèle Model Modelo	Codice Code Code Code Código	Altezza Height Hauteur Höhe Altura H (mm)	Diametro Diameter Diamètre Durchmesser Diámetro Ø (mm)	Lunghezza Length Longeur Länge Longitud L (mm)	Pressione massima d'esercizio Maximun working pressure Pression maximale d'exercice Maximaler Betriebsdruck Presión máxima de trabajo (bar)	Imballo Packing Emballage Verpackung Embalaje (mm)	Attacco Connection Raccordement Anschluss Conexión (inch)
VSI12	AAFTA0OW00BA1	325	280	-	10	(Pz1) 280X285X335	2 X 3/4 "
VSI18	AAGTA0OW00BA1	435	280	-	10	(Pz1) 290X290X450	2 X 3/4 "
VSI24	AAITA0OW00BA1	510	280	-	10	(Pz1) 290X290X510	2 X 3/4 "